



DURO



SAWS

**CHAINSAW
PIPE
RECIPROCATING**

AGP CONCRETE DIAMOND CHAINSAW



RED ROOSTER



CS11 DIAMOND CHAINSAW

- Concrete chainsaw
- 2600W electric motor
- 300 mm depth of cut
- Soft start with LED load feedback indicator
- Electronic protection for over / under voltage - fitted with RCD unit
- Integrated water feed
- Electric and thermal overload protection
- Waterproof / dust-proof hall effect switch
- Bumper spike for increased leverage
- Splash flap for operator protection
- Dual spirit levels
- Cord length of 2.5m - Hose Length of 0.7m

RRI-8560 CHAINSAW

- Concrete chainsaw
- 1.5Kw Air powered motor
- Suitable for heavy industrial use
- Tool can be used in wet environment
- Safety lever start
- 7.6 kg weight
- 355 mm (14") blade
- 340 mm depth of cut
- Low vibration
- Isolating rubber grip handle

Type	Guide Bar Length mm	Plunge Cut Depth mm	No Load Min RPM	Power kW	Power V	Plug Type	Weight inc Chain Kg	Vibration m/s ²	Noise level dB(A)	No Of Chain Links
CS11	382	300	10000	3.0	110 (50Hz)	32A - 5KVA	9.04 kg	4.3	100.5	25

Type	Guide Bar Length mm	Plunge Cut Depth mm	RPM	Power kW	Air cons. l/s	Weight kg	Vibration m/s ²	Noise level dB(A)	Inlet-thread	Hose dia mm
RRI-8560	355	340	18,000	1.5	50	7.6	< 2.5	98	BSP 3/4"	19



RRI-8460



Recip saw blade not included



RRJ-8205



- Supplied in blown vinyl case complete with blades and universal air inlet joint
- Complete with universal swivel joint for greater manoeuvrability

RRI-8460

- Suitable for heavy industrial use
- Large selection of blades available on page 166
- Safety lever start
- Capacity steel: 45 - 530 mm
- Low vibration - 1.7 m/s² vibration level
- 6 and 12" pipe clamps available on page 170

RRJ-8205

- Suitable for industrial use
- Low vibration
- Plastic layer over housing offering good thermal isolation
- Safety lever start
- Hand grip in isolating rubber cover
- Up to 5,000 strokes per minute
- Max steel cutting capacity 10 mm
- Max aluminium cutting capacity 12 mm

Type	Capacity steel Ø mm	Capacity Aluminium Ø mm	Strokes p/min	Stroke mm	Power kW	Air cons. l/s	Weight kg	Inlet-thread	Hose diameter mm	Vibration m/s ²	Noise level dB(A)
RRI-8460	45-530	n/a	300	65	1.1	20	8.0	BSP 3/4"	19	1.7	82
RRJ-8205	10	12	5000	25	0.25	2.8	0.96	PT 1/4"	6.53	3.5	79

CS11 DIAMOND CHAINSAW

Description	Part number
Diamond Chain	305-00035-000-006
Sprocket	305-00403-000-001
Guide Bar	305-00404-000-001



RRI-8560 CHAINSAW

Description	Part number
Chain	91VLX
Guide Bar	140SPET041 DZ



RRI-8460 PIPE CUTTING SAW



Description	Part number	Size	Tpi
Pipe Clamps	8460-200-00 8460-201-01	6" 12"	- -
HSS-Saw Blades USE FOR: TOUGH STEELS UP TO 1100N/mm2 TENSILE STRENGTH (STAINLESS STEEL)	Z22-10 Z22-6 Z22-7 Z22-72 Z22-31 Z22-30 Z22-9 Z22-29	200 x 25 x 1.5 mm 300 x 25 x 1.5 mm 400 x 25 x 1.5 mm 500 x 28 x 2.0 mm 300 x 25 x 1.5 mm 530 x 28 x 1.5 mm 200 x 25 x 1.5 mm 400 x 25 x 1.5 mm	16 teeth/inch 16 teeth/inch 16 teeth/inch 14 teeth/inch 12 teeth/inch 12 teeth/inch 8 teeth/inch 8 teeth/inch
HSS- Saw Blade Carbide Coated USE FOR: CONCRETE, GLASS, HARDENED STEEL AND MORE	Z22CT-06	300 x 25 x 2.0 mm	16 teeth/inch

RRI-8205 RECIPROCATING SAW

Description	Part number	Tpi
5-pack Saw Blades	8205-524-00	24 TEETH/INCH USE FOR: WOOD, PLASTICS, METAL PLATE FROM 2 mm
5-pack Saw Blades	8205-518-00	18 TEETH/INCH USE FOR: ALUMINIUM & METAL PLATE UP TO 2 mm

