AIR ANGLE GRINDERS

Construction,
Automotive & Industrial

YOKOTA

TOKU

TAG-45MLH / TAG-50MLH

INDUSTRIAL

- Vibration level 2.7m/s²
- 4½" Angle grinder 13,000rpm
- 5" Angle grinder 12,000rpm
- M14 Spindle
- Compact & lightweight design
- For cutting, grinding & sanding applications
- Suitable for industrial applications
- Vibration damping side handle
- Silenced exhaust for increased operator comfort

Type	TAG-45MLH	TAG-50MLH
Brand	TOKU	TOKU
Wheel size mm	115 x 6.0* x 22.23	125 x 6.0* x 22.23
RPM	13,000	12,000
Power kW	0.67	0.67
Spindle (Whitworth) mm	M14 x 2	M14 x 2
Air cons. l/s	10.8	10.8
Weight kg	1.80	1.80
Inlet thread	PT 3/8"	PT 3/8"
Hose diameter mm	10.0	10.0
Vibration m/s²	2.7	2.7
Noise level dB(A)	83	83

* Maximum wheel thickness

Vibration Control

A selection of our tools are fully equipped with a range of vibration reducing design features for smoother operation and greater comfort. By selecting a vibration controlled option, you not not only decrease any potential health risks to your tool operators, but you could also massively increase your productivity levels. The vibration control feature increases the length of time the tool can be used before current ELV & EAV levels are reached.

ACCESSORIES

Rubber Pads

Part number	Description
9310-3008-00-00	Disc 100 x 22.23mm
DCA-BP-115xM14	Disc 115 x 22.23

Rubber pad pictured with TAG series grinder

Red Rooster ATLUB Oil

All Toku Industrial grinders should be oiled regularly with Red Rooster ATLUB oil. This will significantly increased the lifetime of the air motor and reduces future service costs.

Part number	Description
ATLUB	Lubricating oil

Standard Flanges & Outer Wheel Screws

Part number	Description
42-05-80-H00*	Outer flange

* Supplied as standard

M14x2 Quick Nut

Part number
QN-M14

Tools for mounting grinding wheels

Part number	Description
13-40-04-014*	Combi spanner 14 x 19
13-08-02-147*	Socket bar

* Supplied as standard

TECHNICAL DATA

Type	A mm	B mm	C mm	D mm
TAG-45MLH	267	85	33	50
TAG-50MLH	267	85	33	50



ELV - Daily Exposure Limit Value
EAV - Daily Exposure Action Value

Product Code	Time to reach ELV (hours:minutes)	Time to reach EAV (hours:minutes)
TAG-45MLH	24.00	6.42
TAG-50MLH	24.00	6.42

REPAIR & SERVICE DEPARTMENT

From the Yokota UK service centre at our Sheffield head office we are able to offer you full service, repair & preventative maintenance.

- FREE no obligation quotations
- 3 month comprehensive warranty on all work carried out
- Fully traceable repair history through our quality management systems
- Only OEM spare parts used
- Complete maintenance advice service

WWW.YOKOTA.CO.UK ORDER LINE: 01909 552471 WWW.DURO-DIAMONDS.COM