



## VL SH1

- Suitable for surface preparation including concrete laying or repairing of cracks
- Good ergonomics & well balanced
- Low air consumption
- Flexible jointed scabblers head for vibration reduction and greater operator comfort
- Fitted with single cruciform tungsten carbide tipped replaceable piston
- Rubber handgrip for temperature isolation

Type	VL SH1
Brand	TRELAWNY
Length mm	520
Blows p/min	2,800
Air cons. l/s	5.6
Weight kg	2.85
Inlet thread	PT 3/8"
Hose diameter mm	10
Vibration m/s <sup>2</sup>	4.6
Noise level dB(A)	91

ELV - Daily Exposure Limit Value EAV - Daily Exposure Action Value		
Product Code	Time to reach ELV (hours:minutes)	Time to reach EAV (hours:minutes)
VL SH1	8.41	2.10



### Vibration Control

A selection of our tools are fully equipped with a range of vibration reducing design features for smoother operation and greater comfort. By selecting a vibration controlled option, you not only decrease any potential health risks to your tool operators, but you could also massively increase your productivity levels. The vibration control feature increases the length of time the tool can be used before current ELV & EAV levels are reached.

### ACCESSORIES

### Cruciform & Bush Piston



For type	Part number	Description
SCABLERS	612.5320	Carbide Tipped Cruciform Piston
SCABLERS	612.5325	Carbide Tipped Bush Piston
SCABLERS	614.5301	Brush Seal



## REPAIR & SERVICE DEPARTMENT

From the Yokota UK service centre at our Sheffield head office we are able to offer you full service, repair & preventative maintenance.

- FREE no obligation quotations
- 3 month comprehensive warranty on all work carried out
- Fully traceable repair history through our quality management systems
- Only OEM spare parts used
- Complete maintenance advice service