

# TIP DRESSERS & HOG RINGERS

## Tip dressers & Hog ringers



YNR-8F



YNR-33L

### Tip Dressers

Type	Brand	Tip capacity mm	RPM	Rotation L/R	Max. jaw capacity kg	Air cons. l/s	Weight kg	Inlet-thread	Hose diameter mm	Vibration m/s <sup>2</sup>	Noise level dB(A)
YNR-8F*	YOKOTA	16	1.400	right	-	6,7	1,2	PT 1/4"	9,5	-	-
TDN-5D	YOKOTA	24	320	right	50	11,7	2,9	PT 3/8"	9,5	-	83
TDN-6	YOKOTA	24	320	left/right	170 / 650	15,8	6,5	PT 3/8"	13	-	84

\* Hand model

Blades for tip dressers are separately available and will be custom made on tip specifications. On request we can supply you with detailed information.

### Hog Ringers

Type	Brand	Max. number of rings	Ring size mm	Trigger-pressure kg	Stroke trigger mm	Air cons. l/s	Weight kg	Inlet-thread	Hose diameter mm	Vibration m/s <sup>2</sup>	Noise level dB(A)
YHR-33	YOKOTA	120	8	0,6	7	0,8	1,5	PT 1/4"	6	1,66	79
YHR-33L*	YOKOTA	120	8	0,6	7	0,8	1,5	PT 1/4"	6	1,66	79

\* Extended nose

FUNCTIONING OF THE YHR-33(L)

Pull the trigger and caulk. The work is completed when releasing the trigger.

Push down

60 Stk./Set

YHR-33/33L  
Dimensions after caulking

DIMENSIONS

Type	A mm	B mm	B* mm	C mm
YNR-8F	257	19,5	-	24
TDN-6	217	161	142	19
YHR-33	346	188	-	-
YHR-33L	361	188	-	-