

AGP



DM12 - WET DRILLING

- Heavy duty drilling applications - wet core drilling only
- Maximum wet core drilling - 350mm (rig mounted)
- Highly efficient 3 Speed gearbox with 2800W motor
- Slow start automatic function to protect core segments
- Aluminium housing for cooling and durability
- Horizontal and vertical spirit level for accurate set up
- Internal management system controls amount of power applied
- LED for overload alert & Anti seize ring for core drill connection
- Oil bath gearbox & mechanical clutch
- Brushed motor



TECHNICAL DATA

Voltage
Input Power
Max Core Diameter
No-Load Speeds
Rated Load Speeds
Weight
Dimensions
Vibration Level
EAV / ELV / Exposure Points (P/H)
Decibel Level
Plug Type
Cord Length
Spindle

DM12

110-120V ~ 50-60Hz
110-120V : 2800W
350 mm
350 (#1), 600 (#2), 1000 (#3)
220 (#1), 370 (#2), 620 (#3)
12.9 kg
550 mm x 155 mm x 210 mm
<1.5 m/s²
EAV - 22 hrs 13 mins • ELV - >24H • EP/H 5
97.0 dB (A)
16 amp - 3.3 KVA Transformer
3m
2 - in - 1 <> 1 1/4" UNC (M), 1/2" BSP (F)