

DURO

YOKOTA

SCARIFY
Concrete Floors

DESCALE
Decks, Tanks &
Steel Surfaces



FLOOR PLANERS / SCARIFIERS

PREP IT
SURFACE PREPARATION TECHNOLOGY™

**PETROL
ELECTRIC**

SCARIFIER—FLOOR PLANEK—DESCALER

WARNING: CUTTER DRUM BELOW



TFP200

- 200mm Floor scarifier
 - Suitable when manoeuvrability is important
 - Removal of hard coatings
 - 3 mm cutting depth
 - 195 mm cutting width
 - Safety dead mans switch fitted as standard
 - Vacuum adaptor fitted as standard
 - Fully adjustable handle-bar: provides greater operator comfort
 - Choice of power source: electric or petrol
 - Accurate depth control: improves overall performance and extends cutter assembly life
 - Drum consists of multiple high impact carbide tipped heads
 - Ideal for removal of: rust, scale, paint, adhesives
 - Ideal for removal of deposits from steel and concrete surfaces in preparation for re-coating
 - Ideal for creating keyed or grooved profiles for non-slip surface applications
 - 50 mm dust extraction ready
- Electric Model Transformer is 5Kva



TFP200-110V



See accessories for TFP200 on page 218

TFP200-PETROL

Type	Weight kg	Working Width mm	Cutter Speed	Max Cutting Depth	Power Source	Engine Type	Height mm	Cycle Hz	Output Power	Vibration m/s ²	Noise level dB(A)
TFP200-PETROL	64	195	1833	3 mm	Petrol	Honda GX	900	-	4.5HP-4.1Kw	10	95
TFP200-110V	72	195	1650	3 mm	110V	-	900	50	3HP-2.2Kw	10	95



TFP260

- 250 mm Floor scarifier
 - 6 mm cutting depth
 - Suitable for larger areas where greater depth of cut is required
 - Safety dead mans switch fitted as standard
 - Vacuum adaptor fitted as standard
 - Fully adjustable handle-bar: provides greater operator comfort
 - Choice of power source: electric 415v-3ph or petrol
 - Accurate depth control: improves overall performance and extends cutter assembly life
 - Drum consists of multiple high impact carbide tipped heads
 - Ideal for removal of: rust / scale / paint / adhesives
 - Ideal for removal of deposits from steel and concrete surfaces in preparation for re-coating
 - Ideal for creating keyed or grooved profiles for non-slip surface applications
 - 50 mm dust extraction ready
- Electric Model Transformer is 5Kva

See accessories for TFP260 on page 218



Type	Weight kg	Working Width mm	Cutter Speed	Max Cutting Depth	Power Source	Engine Type	Height mm	Cycle Hz	Output Power	Vibration m/s ²	Noise level dB(A)
TFP260-PETROL	145	250	1500	6 mm	PETROL	HondaGX	1010	50/60	8HP-6Kw	8.8	102
TFP260-415V	158	250	1500	6 mm	415v-3ph	-	1010	50/60	7.5HP-5.5Kw	2.4	102



Drum Replacement

For type	Part number	Description
TFP200	320.1020ST	Complete Replacement Planer Drum inc. TCT heads
TFP260	326.1016ST	Complete Replacement Planer Drum inc. TCT Heads



TCT Cutters

For type	Part number	Description
TFP200	320.5500	TCT Cutter
TFP260	320.7009	TCT Cutter

*TFP200 - 80 per set / TFP260 - 123 per set



Washers

For type	Part number	Description
TFP200	320.4140	Spacer
TFP260	320.4160	Spacer

*TFP200 - 90 per set / TFP260 - 129 per set

